

Gas Electronic Leak Detector LD239

An electronic leak detector is indispensable for finding small leaks around fittings or hot inlets on which a liquid cannot be used. Leak check solutions may contain material that can leak into the gas-supply lines or columns and cause ghost peaks or other contamination.

The LD239 leak detector uses a small pump to pull air from the probe through a thermal conductivity cell. The presence of carrier gas or Hydrogen changes the thermal conductivity and causes a change in the detector's readout compared to a reference air flow.

Ziemer Partnumber: 098LD-1



- Super Compact and Light (only 95 g)
- LCD and LED Displays
- Highly Sensitive – 0.0005 ml/min (He)
- USB Port Rechargeable



ZIEMER Chromatographie

Postfach 1208 · 52374 Langerwehe
Telefon 024 23 / 40493-5 · Fax 024 23 / 40493-88
E-Mail: info@ziemer-chromatographie.de
www.ziemer-chromatographie.de

Gas Electronic Leak Detector LD239




Specifications:

- Detection method:** Thermal conductivity
- Target gases:** Helium, Hydrogen, CO₂, Argon, Neon and other non-corrosive gases. For safety reasons, LD239 should not be used: 1) in places with a risk of fire, explosion or large flammable gas leaks; 2) in places with insufficient ventilation when attempting to detect trace amounts of flammable gases; 3) in places that are contaminated with dust or combustible fumes.
- Sensitivity:** Standard range - minimum 0.005 ml/min (He)
High range - minimum 0.0005 ml/min (He)
- Settings:** Sensitivity Range: (Standard/High), Buzzer: ON/OFF, LED Display: ON/OFF
LCD Backlight: ON/OFF, Auto power shutdown: ON/OFF
- Temperature range:** 10 - 40°C (non-condensing)
- Battery:** Rechargeable Lithium ion battery (up to five hours continuous use). Battery is rechargeable through USB port (2.5 hours for a full recharge).
- Dimension:** 50(W) x 19.5(D) x 111(H) mm
- Weight:** Approx. 95 g
- Accessories:** USB cable, instruction manual, AC-DC adaptor with EURO or UK plug (optional).

Accessories:

Battery for LD239	2702-19341
AC-DC Adaptor, w/o Plug (USB, 5V, 500 mA)	G400006
Input Plug AC-DC Adaptor, EURO	G200010
Input Plug AC-DC Adaptor, UK	G200011
USB cable	2702-19331
Sample Filter	2702-19333



ZIEMER Chromatographie

Postfach 1208 · 52374 Langerwehe
Telefon 024 23 / 40493-5 · Fax 024 23 / 40493-88
E-Mail: info@ziemer-chromatographie.de
www.ziemer-chromatographie.de